I, Hereby certify that the foregoing is a true copy β of field notes of survey of Road #539.

C. W. Macomber, County Surveyor Say one of field notes survey road no. 539 page 2 sparts page Dist. 426' Course N.87°29'T L. R. 7°08' on of TOtal Dist. will faith-S. 85°235 264' 2036' S.64°47'1 690 above 210 11°06' S.75°53'T 900 131 2°13' S.78°06'T 1031 210 1°58' S.80°04'E 1250 350 840 \$88°44'E 1600 278 13º11' \$75°33'E 1878 226 7°27' \$68°06'E 2104 266 19°34' S48°32'E 2370 212 18°58' \$67°30'E 2582 318 \$°50 \$76°20'F 2900 338 13°40' \$62°40'T 3238 424 16°04' 578°44'E 3662 183 14º17' N65.59'T 3845 100 30°50' \$62°11'E 3045 335 8°18' d No 539 S53°53'E 4270 270 2°07' met S56°00'E 4540 236 28°14' re by him \$84°14' 17 4776 504 2°18' appointment \$86°32' 5280 1 mile post 3°50 375 5655 N89°38'E 491 5°37' 6146 N84º01'E 9°04' 141 6287 N74°57'E 313 21°06' 6600 S83°57'E 202 11°15 6892 \$72°42' said Poad 208 7°08' 7100 \$79°50'E some kind 130 34°39' 7230 s way should In the matter of Viewing, surveying and laying out County Poad No.548. To the HOnorable County Court of the State of oregon for Umatilia County. We, the undersigned, the Viewers heretofore appointed to view and locate Poad no548 i we would ROAD 'No an one hun submit the following report: Pursuant to an order of the HOnorable Court we met John W. Kimbrell Surveyor, at Court House in Pendleton, on the 20th day of October, 1902 and were by him each duly sworn to faithfully and impartially discharge the duties of our appointments. We called to our aid Jerry Barnhart | Chainmen D. L. Fubbert | Chainmen County ginning d Road B. B. Crowner Marker marker Who were by the Surveyor, each day sworn. We viewed, surveyed and located said Road No.548 as specified in our order and find the Roat Practicable and would most respectfully which point recommend the same be established as a Public Highway of Umatilla County, Oregon. W. D. Hansford (B. F. R"nn Viewers Foad Survey No 548 Filed. Oct. 21. 1902 J: S. McLeod | UD Chamberlain blut Field notes of ToAd No 548. Commencing at a point 20 chains West of the S. E. Corner of Secl in T 2 N. R. 31 E. W. M. I set post 4 feet long 4 inches Square 20 feet North of Initial point marked R. N.o.548 al Dist des pits ". & ". and built mound of earth 18 inches high 4 feet wide at base of post Thence Wast 33.00 chains 4035 Dist A 2. s. 68°F 735 Chains A 3 A 4 84°F 470 Chains N 4505 443 Cahins 4948 N 58°F N39° E A 5 5228 280 S 78°5 A6 6298 1070 0 W. W. R. 臣. = 8000 One mile set post 4 feet long 1702 4 inches square 20 feet South Marked 1.M. dug pits and raised mound of earth 18 inches high A7 4 feet at base thence Fast 7090 chains A 8 Thence S. 29° F. 425 Chains " \$66° 380 " 7515 7895 R. T. Set post 4 feet long 4 inches square marked P T. No. 548 dug pits F & W and built mound of earth 18 ins. aigh 560 2 mile post 4 feet wide at base around post I hereby certify that the foregoing are correct copy of field notes of road No.548 as surveyed by me on the 20th day of October, 1902 John W. Kimbrell, County Surveyor 250 End of survey 7 7 30 ft, So d of survey

36 05

57

13

350

145

rveyor