

FIELD NOTES OF COUNTY ROAD NO. 711.

I commence at the N. W. corner of Sec. 4, T. 4 N., R. 23 E., W. M. At a point 30 ft. S. and 30 ft. W. of aforesaid point I set a post, 4 ft. long, 4 ins. square, marked R. 711; dug pits 18 x 18 x 18 ins., N. & S. of post, and raised mound of earth, 18 ins. high, 4 ft. base, around post. ^{80.00 chs.}
Thence following the section line South to a point from which I set, to the right 30 ft. distant, a post, 4 ft. long, 4 ins. square, marked 1 M; dug pits, 18 x 18 x 18 ins., N. & S. of post, and raised mound of earth, 18 ins. high, 4 ft. base, around post.

Thence following the section lines south ^{0.80} chs. to irrigation ditch
" S. " " " " ^{19.58} " " angle 1
,, S. 61° 37' W. 11.84 chs. to angle 2
,, S. 48° 31' W. 8.00 ,, , , , 3
,, S. 62° 47' W. 8.00 ,, , , , 4
,, S. 34° 33' W. 8.16 ,, , , , 5
,, South 6.45 ,, , , , 6
,, S. 36° 36' E. 13.43 ,, , , , 7
,, S. 30° 55' E. 3.75 ,, a point from which I set, to the left 30 ft. distant, a post, 4 ft. long, 4 ins. square, marked 2 M; dug pits, 18 x 18 x 18 ins., N. & S. of post, and raised mound of earth, 18 ins. high, 4 ft. base, around post. Thence S. 30° 55' E. 6.06 chs. to angle 2 Thence S. 13° 23' E. 14.89 chs. to line between Secs. 8 & 17 in said township and range, angle 9 Thence east 5.45 chs. to west end of County steel bridge from which I set, 30 ft. S. & 35 ft. W. a post, 4 ft. long, 4 ins. square, marked R. T. 711; dug pits W. & S. of post, and raised mound of earth, 18 ins. high, 4 ft. base, around post.

I hereby certify that the foregoing field notes
of County road No. 711 are correct according to survey made
by me; commenced on the 23^d day of May, 1911.

Geary Kimball
Surveyor for Umatilla County, Oregon.