

Q-582-Ax ORIG

TRACTS OF LAND

IN

THE S.E. 1/4 OF N.E. 1/4 OF S.E. 1/4 OF SECTION 3,
TWP. 4N., R. 28E., W.M.

UMATILLA COUNTY, ORE.



SCALE: 1" = 100'

Coulson

3/4 I.P.

NW Cor of S.E. 1/4
of N.E. 1/4 of S.E. 1/4

N. 89° 42' W

615.73'

S. 0° 18' W

1/32.8

1/P

20'

1/P

June 15, 1950

FIELD NOTES

For tracts of land in the S.E. $\frac{1}{4}$ of N.E. $\frac{1}{4}$ of S.E. $\frac{1}{4}$
of Section 3, Township 4 North, R. 28 E., W.M.

BY V.R. Fraley
Ore Land Surveyor #183

The survey of the tracts as shown on the accompanying sketch
is based on my re-survey of the S.E. $\frac{1}{4}$ of the said Section 3.

I began the survey at a 5/8" Iron Pin which is the East $\frac{1}{4}$ corner
of Section 3, establishing line between that point and a 5/8" Iron
Pin which is the Section corner common to Sec's 2-3-10-11. I used
the bearing of N.0°-21'E for this section line which is the bearing
computed by the Oregon State Highway Dept.

Q-582-Ax