Bonneville Power Administration Geodetic Control Data Sheet

Station:	WM050 (250)						
Project:	Wallula-Smiths Harbo	r-McNary					
Section:	SE 1/4 19	Township: 5	North	Range:	29 East	Meridian:	Willamette
County:	Umatilla	State: C)R	USGS Quad:	Hat Rock, Ore		-
Surveyor:	M R Heidecke			Date Surveyed:	-	3	

Instrument:

The horizontal coordinates and orthometric elevation were established by GPS observations using six Trimble 4000 SSI dual frequency receivers with Compact L1/L2 antennae with ground plane.

Adjustment:

The Basis of Coordinates for this survey is the Oregon State Coordinate System, North Zone, NAD 83 (1998). The horizontal component of the least squares adjustment was constrained by holding NGS Stations B 340 (A), B 502 (B), PENDLETON (B), STANFIELD EAST BASE RESET (B), and BURDEN (B). The vertical component of the least squares adjustment was constrained by holding NGS Benchmarks B 340 (First Order Class II), B 502 (First Order Class II), BURDEN (Second Order Class II), V 203 (Second Order Class 0), G 640 (First Order Class I). The elevation for point 106, 201, 249, and 255 were determined by differential leveling from G 640, D 502, E 525 and F 431 respectively and held.

Horizontal Datum: Vertical Datum:		_NAD83 (1998) _NAVD88		Linear Unit:	_International Feet _U.S. Survey Feet	
				Linear Unit:		
Latitude:	N 45-53	-57.62876	Longitude:	: W 119-13-25.9	96836	
US State F	Plane Coor	dinate System:		Oregon North		

US State Plane Coordinate Syste	em:	Oregon North Zone - 3601
Northing: 816,563.972	Easting	8,526,985.104
Orthometric Elevation: 4	66.63	Ellipsoid Height: 395.41
Combined Factor: 0.9999	95710	Convergence: - 0-54-18
Confidence: 95% Confidence ("1	.96 Sigma") Valu	ues .
Northing-0.009	Easting-0.	007 Elevation-0.105

Monumentation: BPA 3¼-inch Aluminum Cap on 5/8-inch aluminum rod, flush with ground. Stamping: U.S.D.O.E. Bonneville Pwr. Adm., WM050 - FEC-01 - ATB - GPS

To-Reach Description:

Begin at Umatilla Post Office, Umatilla, OR. 97882. Drive east on Highway 730, 5.3 miles to intersection of Craig Road to the right (south). Drive south on Craig Road 0.5 miles to the station on right (west) side of road. Station is 15 feet from west edge of Craig Road and 9 feet east of barb wire fence..

Witness post is a yellow carsonite marker inscribed with BPA logo, bearing and distance to station.

RECEIVED BY

Canada Andreas Andreas Andreas
Umatilla County Surveyor
Date
Rec'd By
No. 02-19-01