## Bonneville Power Administration Geodetic Control Data Sheet

Station:	VVM031 (231)						
Project:	Wallula-Smiths Harbor-McNary						
Section:	NE 1/4 1	Township: 5 North	Range:	20 East			
County:	Umatilla	State: OR		_30 East	Meridian:	_Willamette	
Surveyor:	M R Heidecke		USGS Quad: Juniper Canyon, Oregon Date Surveyed: July, 2001				
	<del></del>		Date Surveyed.	July, 2001			

## Instrument:

The horizontal coordinates and orthometric elevation were established by GPS observations using six Trimble 4000 SSI dual frequency receivers with Compact L1/L2 antennae with ground plane.

## Adjustment:

The Basis of Coordinates for this survey is the Oregon State Coordinate System, North Zone, NAD 83 (1998). The horizontal component of the least squares adjustment was constrained by holding NGS Stations B 340 (A), B 502 (B), PENDLETON (B), STANFIELD EAST BASE RESET (B), and BURDEN (B). The vertical component of the least squares adjustment was constrained by holding NGS Benchmarks B 340 (First Order Class II), B 502 (First Order Class II), BURDEN (Second Order Class II), V 203 (Second Order Class 0), G 640 (First Order Class I). The elevation for point 106, 201, 249, and 255 were determined by differential leveling from G 640, D 502, E 525 and F 431 respectively and held.

	IAD83 (1998) IAVD88	Linear Unit: Linear Unit:	International Feet U.S. Survey Feet			
Latitude: N 45-56-56.		Longitude: W 118-59-50.62409				
US State Plane Coordina Northing: 835,671.873		Oregon North				

 Northing:
 835,671.873
 Easting
 8,584,302.317

 Orthometric Elevation:
 1122.21
 Ellipsoid Height:
 1051.76

 Combined Factor:
 0.99993727
 Convergence: 1-03-56

 Confidence:
 95% Confidence ("1.96 Sigma") Values

 Northing-0.008
 Easting-0.005
 Elevation-0.105

Monumentation: BPA 31/4-inch Aluminum Cap on 5/8-inch aluminum rod, 1.5 feet below ground.

Stamping: U.S.D.O.E. Bonneville Pwr. Adm., WM031 - FEC-01 - ATB - GPS

## To-Reach Description:

Begin at Umatilla Post Office, Umatilla, OR. 97882. Drive east on Highway 730, 9.2 miles to intersection of State Highway #37 to right (south). Drive southeasterly on State Highway #37, 1.3 miles to intersect BPA 500kV transmission line crossing Highway #37 northeast to southwest. Drive northeasterly on the transmission line access road 6.2 miles to tower 47/2.

Witness post is a yellow carsonite marker inscribed with BPA logo, bearing and distance to station.

RECEIVED BY
Umatilla County Surveyor
Data
Rec'd By
19-0