## Bonneville Power Administration Geodetic Control Data Sheet

Station:	WM038 (238)					
Project:	Wallula-Smiths Harbor-M	1cNary				
Section:	SE 1/4 9	Township: 5 North	Range:	30 East	Meridian:	Willamette
County:	Umatilla	State: OR	USGS Quad:	Juniper, Orego		_ vviliai i i elle
Surveyor:	M R Heidecke		Date Surveyed:		<b>,</b> , , , , , , , , , , , , , , , , , ,	

## Instrument:

The horizontal coordinates and orthometric elevation were established by GPS observations using six Trimble 4000 SSI dual frequency receivers with Compact L1/L2 antennae with ground plane.

## Adjustment:

The Basis of Coordinates for this survey is the Oregon State Coordinate System, North Zone, NAD 83 (1998). The horizontal component of the least squares adjustment was constrained by holding NGS Stations B 340 (A), B 502 (B), PENDLETON (B), STANFIELD EAST BASE RESET (B), and BURDEN (B). The vertical component of the least squares adjustment was constrained by holding NGS Benchmarks B 340 (First Order Class II), B 502 (First Order Class II), BURDEN (Second Order Class II), V 203 (Second Order Class 0), G 640 (First Order Class I). The elevation for point 106, 201, 249, and 255 were determined by differential leveling from G 640, D 502, E 525 and F 431 respectively and held.

Horizontal Datum:	NAD83 (1998)	Linear Unit:	International Feet
Vertical Datum:	NAVD88	Linear Unit:	U.S. Survey Feet
1 -11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			

Latitude: N 45	5-55-21.13586	Longitude	: W 119-03-35.41	533		
US State Plane C	coordinate System:		Oregon North Zone - 3601			
Northing: 825,	723.406	Easting	8,568,593.482			
Orthometric Eleva	ation: 887.6	5	Ellipsoid Height:	816.99		
Combined Factor	0.9999422	5	Convergence: -			
Confidence: 95% Confidence ("1.96 Sigma") Values						
	hing-0.009	Easting-0.		Elevation-0.107		

Monumentation: BPA 31/4-inch Aluminum Cap on 5/8-inch aluminum rod, flush with ground. Stamping: U.S.D.O.E. Bonneville Pwr. Adm., WM038 - FEC-01 - ATB - GPS

## To-Reach Description:

Begin at Umatilla Post Office, Umatilla, OR. 97882. Drive east on Highway 730, 9.2 miles to intersection of State Highway #37 to right (south). Drive southeasterly on State Highway #37, 1.3 miles to intersect BPA 500kV transmission line crossing Highway #37 northeast to southwest. Drive northeasterly on the transmission line access road 2.9 miles to intersection of a Pacific Power & Light 230kV transmission line at PP&L structure 2/16. The station is 228 feet northeast of the center of PP&L structure 2/16.

Witness post is a yellow carsonite marker inscribed with BPA logo, bearing and distance to station.

RECEIVED BY
Smatilla County Surveyor
Date
Red'd By
02-9-9
02-9-9