## Bonneville Power Administration Geodetic Control Data Sheet

Station:	WM032 (232)					
Project:	Wallula-Smiths Harbor-McNary					
Section:	_NW 1/4 6	Township: 5 North	Range:	31 East	Meridian:	Willamette
County:	Umatilla	State: OR		_Juniper Canyo		
Surveyor:	M R Heidecke		Date Surveyed:		n, Oregon	
				-		

## Instrument:

The horizontal coordinates and orthometric elevation were established by GPS observations using six Trimble 4000 SSI dual frequency receivers with Compact L1/L2 antennae with ground plane.

## Adjustment:

The Basis of Coordinates for this survey is the Oregon State Coordinate System, North Zone, NAD 83 (1998). The horizontal component of the least squares adjustment was constrained by holding NGS Stations B 340 (A), B 502 (B), PENDLETON (B), STANFIELD EAST BASE RESET (B), and BURDEN (B). The vertical component of the least squares adjustment was constrained by holding NGS Benchmarks B 340 (First Order Class II), B 502 (First Order Class II), BURDEN (Second Order Class II), V 203 (Second Order Class 0), G 640 (First Order Class I). The elevation for point 106, 201, 249, and 255 were determined by differential leveling from G 640, D 502, E 525 and F 431 respectively and held.

Horizontal Datum:	NAD83 (1998)	Linear Unit:	International Feet
Vertical Datum:	NAVD88	Linear Unit:	U.S. Survey Feet
1 -414 1 1 1 4 7 7 7			

	V 45-56-50.6		Longitude	: W 118-59-27.39	521
US State Plan	ne Coordinat	e System:		Oregon North Zo	one - 3601
Northing: 8	35,113.947		Easting	8,585,954.371	
Orthometric E		1060.74		Ellipsoid Height:	990.33
Combined Fac		0.99993981		Convergence: -	
Confidence: 95% Confidence ("1.96 Sigma") Values					
	Northing-0.0		Easting-0.		Elevation-0.106

Monumentat	on: BPA 31/4-inch Aluminum Cap on 5/8-inch aluminum rod, flush with gro	und
Stamping:	J.S.D.O.E. Bonneville Pwr. Adm., WM032 - FEC-01 - ATB - GPS	ana.

## To-Reach Description:

Begin at Umatilla Post Office, Umatilla, OR. 97882. Drive east on Highway 730, 9.2 miles to intersection of State Highway #37 to right (south). Drive southeasterly on State Highway #37, 1.3 miles to intersect BPA 500kV transmission line crossing Highway #37 northeast to southwest. Drive northeasterly on the transmission line access road 6.2 miles to tower 47/2. Pack S 45° E, 180 feet from tower center to the station.

Witness post is a yellow carsonite marker inscribed with BPA logo, bearing and distance to station.

-	EIVED BY		<b>'01</b>
Dets			_
Bec'd B	y		~
No.	) 2 - / (	) <u>-(</u>	Ł
			-