


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner originally established by Timothy W. Davenport under GLO contract number 102, dated July 20, 1863. Surveyor General record states: Set qr Sec post on top of table land in edge of timber, from which post;
 A Tamarack 6 inch in dia bears N40°W 25 lks
 A Tamarack 16 inch in dia bears S50°W 40 lks



Corner reestablished by Herman D. Gradon under GLO contract number 452, dated June 16, 1882. Surveyor General record states:
 Set a post 3 ft. long 3 ins square 24 ins in the ground for ¼ sec cor marked BL ¼ S on N. face from which:
 A tamarack 8 ins diam bears N30°W 12 lks dist marked ¼ S BT
 A tamarack 20 ins diam bears S30°W 37 lks dist marked ¼ S BT
 The old ¼ sec cor a post bears W. 70 lks dist. I destroy same and obliterate marks on old bearing trees, 2 tamaracks.

No record of subsequent monumentation found in Umatilla County survey records.

Description of corner evidence found:

Found no evidence of the original corner monument or it's accessories.

See map of survey dated September, 1989.

Description of monument and accessories I established to perpetuate the

original location of this corner: At position determined by survey, I set a 2½" x 30" aluminum pipe with aluminum cap marked as shown, 28 inches in the ground, from which:

New Bearing Trees:

A 10 inch diameter Douglas Fir bears N30°E, 20.26 feet marked ¼ S36 SC BT
 A 20 inch diameter White Fir bears N45°W, 19.27 feet marked X BT


Painted a 6 inch red band around all BTs and attached bearing tree and land survey monument signs.

Set a steel fencepost approximately 5 feet East with Land Survey Monument sign attached.

Raised a mound of stone around monument, 2 ft. base to top of cap.

I hereby certify that the above corner point was perpetuated as hereon described on August 15, 1989.

Witnesses: Rick Robinson and Jeff Petersen.



I used a steel tape and magnetic compass in the establishment of new accessories. I used 17° East magnetic declination and the distances are to a 50d spike driven in the right side of the root crown. I attached a brass washer marked OPLS 644 to the BT blaze.

Office of the Survey Dept. County of Umatilla
 State of OR, I hereby certify that the within instrument was filed in this office for record on the 27th day of October, 1989
 David H. Krumbein by Kathleen K. Amosberg
 (COUNTY OFFICIAL) (DEPUTY)

RECEIVED BY
 Umatilla County Surveyor
 Date 10-89
 Initials KA
 59-151-B