


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1882 by Herman D. Gradon, under General Land Office Contract No. 452.

Surveyor General Records (notes) states:  
Set a basalt stone 14 x 10 x 4 ins. 9 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on N face from which a pine 30 ins. diam. bears N 57° W 106 lks. dist. marked 1/4 S BT. A pine 30 ins. diam. bears S 20° W 283 lks. dist. marked 1/4 S BT.



J. 23

(No subsequent remonumentations in county records)

Description of corner evidence found:


Found 36 in. pine, live in good condition, with scribing visible.  
Established corner position N 20° E 186 ft. dist. from tree.

Description of monument and accessories established to perpetuate the original location of this corner

Set 30 in. x 2 1/2 in. iron pipe with 3 in. brass cap marked as shown, 25 in. in the ground and raised a mound of stone around pipe for the 1/4 corner between Sections 12 and 13, from which a new BT - a 30 in. pine bears N 27° W 150 ft. dist. marked T1S R36E 1/4 S 12 BT. Distance taken to a brass washer in the blaze of the tree.

Set a steel fence post approximately 5 ft. E of corner with "Attention" sign attached.

Used steel tape and magnetic compass with declination = 20° East.



REGISTERED  
PROFESSIONAL  
AND SURVEYOR

*Douglas M. Ferguson*  
OREGON  
JULY 12, 1953  
DOUGLAS M. FERGUSON  
848

Office of Surveyor County of Umatilla  
State of Oregon, I hereby certify that the within Instrument was filed in this office  
for record on the fourth day of October; 1972, at 12 o'clock noon, (signed)  
Douglas M. Ferguson by Douglas M. Ferguson  
(COUNTY OFFICIAL) (DEPUTY)