USDA-FOREST SERVICE Index File NoE-9	CORNER RECORD (SEARCH) Tract or Cor. Section Survey No No
T4S R32E	R.D. <u>Ukiah</u> County <u>Umatilla</u>
Merid. <u>Willamette</u>	N.F. <u>Umatilla</u> State <u>Oregon</u>
CORNER DIAGRAM	DESCRIBE CORNER MONUMENT FOUND
S5   S4	Ground was torn up by logging equipment. Found two parts of a stone, with marks, lying loose in the vicinity.
γ <del></del>	DECORING DEADING TORSE OF THE PROPERTY OF THE
S8 S9	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND
	No trees were marked as bearing trees according to original notes.
PHOTO IDENTIFICATION DATA	<del>-</del>
Photo No.	
Filed At.	
Object Ident	DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER
Ident. By	
PLANE COORDINATE POSITION DATA State Zone	The corner is on a slight south slope about 300 feet north of the bottom of a gully with a small stream. In a heavily logged area.
X	103304 4164.
Υ	
Estab. By	
1.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Title Division Headquarters Date 7100 To (0.17)

CORNER RECORD (PERPETUATION)		GPO 902-678
MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT	T4S R32E	
Set 2½" x 30 galvanized pipe with brass cap marked:	S5 S4	
Pipe is set 22" in ground. Mound of stone to cap. Buried stone found in the vicinity at base of pipe.	S8 S9 1977 OR PLS 10	51 ,
ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESER Fir 14" in dia. bears N13°W, 29.0 ft., scribed T4S R32E S5 BT. Fir 14" in dia. bears N48°E, 14.0 ft., scribed T4S R32E S4 BT. Fir 14" in dia. bears S60°E, 9.0 ft., scribed T4S R32E S9 BT. Fir 11" in dia. bears S72°W, 20.0 ft., scribed T4S R32E S8 BT. Attached brass washer, stamped PLS 1051, to foot blaze of all BT's. Attached 54-3 and 54-4 signs to all B.T.'s. Het painted metal fence post 3 ft. north of monument with 54-4 signs		N CE
et painted metal fence post 3 ft. north of monument with 54-4 sign ainted a 6" band around each B.T. and both blazes on each B.T. red		10
Work Done By R.C. Orton title Party Chief Date 11-1-7 State Registral	ion No.	<u>.</u>
Certified Cor. Record Prepared ? Yes No Filed At:	Date	11
REMARKS		
ditnesses to the above corner: G. Wagoner L. Clemens		

Index File No.

T.

R.

M.

Tract or Surv. No.

Cor.

13

USDA-FOREST SERVICE GPO 940	E-9
Index File No F - 9	CORNER RECORD (SEARCH) Tract or Cor.
	R.D. UKIAI (Ref. FSM 7151.4) Survey No No No
Merid	N.F. UMA+I/A State ORC.
CORNER DIAGRAM	DESCRIBE CORNER MONUMENT FOUND
5	Stone 18"x 12"x 6", with 3 noteles on one side And 1 notch on other side
	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND  A 24" DBH. Pine with blaze brs. 5.55° w. 15 ft.
PHOTO IDENTIFICATION DATA Photo No Filed At.	A. 30" stump with blaze berrs 5, 45°E. 33 Ft. There is A 4 Ft x 4 Ft, x 3 Ft, Rock stack N_35°E, 110 Ft.
Object Ident.  Ident. By Signature 7	DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER  TROM 5-37 In See, 5, Take Fire ROAD 5 FOR .05 miles,
PLANE COORDINATE POSITION DATA State Zone X Y	on skid trail and got 500 Ft., rock stack is
Estab. By	on All the transfer of the Helpholes of the Selection of
Signature W.L. WA	Ken Title Division Headquarters U/t/Air Date 7100-52 (3/68)

7.274.

	CORNE	ER RECORD (PERPE	TUATION)	
MONUMENT: DESCRIBE NEW	MONUMENT SET, OR WORK DO	NE TO PRESERVE EXISTI	NG MONUMENT	
ACCESSORIES . DESGRIDE .	12 5. 0	0. 201452101125, 01. 1101	RK DONE TO PRESERVE EXISTING EV	
			·	
•				
•				
·				
			<u> </u>	
Work Done By	Tifle	Date	State Registration No.	
Work Done By Certified Cor. Record Prepo			State Registration No. or Agency	

Index File No. E- 9 T. R. M. Tract or Surv. No. Cor. 13