USDA-FOREST SERVICE	
Index File No. 6-12	CORNER RECORD (SEARCH) Tract or Cor. a - 1/1
T 45 R. 32E	R.D. Ukiah County Umatila
Merid Willamette	
CORNER DIAGRAM	N.F. Umatilla State Oregon
	DESCRIBE CORNER MONUMENT FOUND
T4S R3ZE	Found 2" GIP W/ 21/2" BC PLS 1051 1977
1	Mos
NCE - 16	D5000105 0540110 050000 05000000
	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND
l	G. Fir "dian, Brs SB3°19'W FT
5 (
	G. Fir "dia, Brs N78° 57'E FT
PHOTO IDENTIFICATION DATA	G, FIF May dis 1470 37 E F
Photo No.	
Filed At.	
Object Ident	DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER
Ident. By	
Signature 7	INTERSECTION Rd 5417 And 5417; SOUTH Rd 5417
PLANE COORDINATE POSITION DATA	
State Zone	1.5 mi TO NATIONAL FOREST BOUNDARY LINE;
x	BUE WEST OIL MI TO CE VIB COR.
Υ	000 0031 010 100 100 100 1010,
Estab. By	
Signature /	Title Division Headquarters
Suit P Selección	7100-52 (3.68)
June C massion	P.L.S. 12/11/80 1200-52-(3,68) 5

ı

CORNER RECORD (PERF	
MONOMENT SESSMENT REW MONOMENT SET, OR WORK DONE TO PRESERVE EXIS	TING MONUMENT
•	
ACCESSORIES OF DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR W	ORK DONE TO PRESERVE EXISTING EVIDENC
	·
Work Done By K.C. Weaver Title PLS , Dote 124	11/80 State Registration No. 1679
Certified Cor. Record Prepared ? Yes No & Filed At:	Date
	Date
REMARKS	

M.

Tract or Surv. No.

Cor.

13

Index File No.

T.

R,

Index File NoG-12 T4SR32E	CORNER RECORD (SEARCH) Tract or Cor. CE1/16 R.D. Ukiah County Umatilia
Merid. W.M.	N.F. Umatilla State Oregon
CORNER DIAGRAM	DESCRIBE CORNER MONUMENT FOUND
/	None set.
T4S R32E W.M.	
CE 1/16 S9	2
CE 1/10 39	DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND
C C	None set.
PHOTO IDENTIFICATION DATA	<u>-6</u>
Photo No.	
Filed At.	3
Object Ident Ident. By	DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER
Signature	The corner lies on a fairly steep east slope about
PLANE COORDINATE POSITION DATA	700 feet east of a logging road.
State Zone	
×	_
Υ	_ `
Estab. By Agency	-
avery Blackou	Title Division Headquarters Date 7100-52 (3/68) WY P.L.S. 11/8/77 5
	4+1 V 1 1

·--:

A fir 17" in dia. bears N84^OE, 9.0 ft., scribed CE1/16 S9 BT. A fir 11" in dia. bears S86^OW, 24.7 ft., scribed CE1/16 S9 BT. Attached brass washer, stamped PLS 1051, to the foot blaze of each B.T. Attached a 54-3 and a 54-4 sign to each B.T. Set a painted metal fence post 6 ft. south of monument with a 54-2 and a 54-9 sign attached. Set another post 3 ft. east of monument with a 54-2 and a 54-4 sign attached. Painted a 6" band around each B.T. and both blazes on each B.T. red.

!	<u> </u>		·	10
Work Done By	R.C. Orton	e Party Chief	Date 11/8/77State Registration No.	v-
Certified Cor. R	ecord Prepared ? Yes N	o Filed At.	Date	11_
Ş.	;	REMARKS		

Tract or Surv. No.

Witnesses to the above: G. Wagoner, L. Clemens

R.

ndex File No.

Cor.