INDEX No. P-25

History of original corner establishment:

This corner was originally established George
Pershin, in 1881, under GLO Contract No. 390.
Surveyor General Field Notes state:

T4S 1/4 R32E R33E S24|S19 1994 PLS 2405

DIAGRAM

Set basalt stone 18x12x5 in ravine on west bank of brook for 1/4 sec. cor.

A tamarack 20 in. dia. brs N45°E, 26 lks. dist. A fir 8 in. dia. brs S42°W, 60 lks. dist.

Description of Corner Evidence Found:

None. Found several stones of near record size 18x12x5, however no marks. The search area fell on the west bank of stream. Looked on both sides, nothing found.

Old logging in the area and I believe the bearing trees were lost to this logging.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set 2-1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the DIAGRAM, 18" in the ground and raised a mound of stone around the monument.

From Which:

Western Larch, 20" dia., bears N36°16'W, 87.0 ft., scribed: 1/4 S24 BT Spruce, 14" dia., bears N38°57'E, 37.1 ft., scribed: 1/4 S19 BT Western Larch, 28" dia., bears S81°52'E, 37.6 ft., scribed: 1/4 S19 BT Spruce, 24" dia., bears S55°24'W, 63.8 ft., scribed: 1/4 S24 BT

Measurements to BT's taken with an Electronic Tacheometer with bearings based on the survey control network. Set steel fence post with Land Survey Monument (54-9) sign 5' north of the monument. Nailed a brass washer stamped PLS 2405 on blaze above BT scribe as taken this survey. Nailed Bearing Tree (54-3) signs above blaze and Land Survey Monument (54-9) signs on back of each tree as required. Painted a 6" red band above Bearing Trees signs.

PROFESSIONAL LAND SURVEYOR

LAND SURVEYOR

OREGON
JULY 26, 1969
SUSAN E. NEWSTETTER
2405

This work was performed by: Susan E. Newstetter PLS 2405 Witnessed by: Rick Saul and Rick Pewonka October 21, 1994

Unactive Day

Unactive Day

Data 1-95

Rac d 37 45

No. 95-/5-B