


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established in 1882 by Rufus S. Moore under General Land Office Contract No. 451.
 Surveror General Records state:
 Set basalt stone 24 X 15 X 15 ins. for cor. to secs 1, 2, 35, 36; dug pits.



No record of subsequent remonumentation was found in county records.


Description of corner evidence found:

Found stone 24" X 15" X 12" faintly marked in a mound of stone.

(See map of Survey, dated December, 1975)

Description of monument and accessories established to perpetuate the original location of this corner

At corner position I set 2 1/2" X 30" iron pipe with brass cap marked as shown 14 " in ground, from which:
 A 8" Pine bears S 6° E, 430.3 ft. marked T5S R331/2E S1 BT.
 A 14" Pine bears S 17° W, 357.4 ft. marked T5S R331/2E S2 BT.
 No other trees or bearing objects available within a 1000 ft. of the cor.
 Buried stone South and along side pipe.
 Raised mound of stone 6 ft. base to top of cap.
 Set steel fence posts 5+ ft. East and North.



REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

OREGON
 JULY 10, 1954
 DUANE I. GRIFFITH
 644

Brass Washer nailed to BT blazes.
 Used steel tape and magnetic compass with 19° 30' East declination.
 Measured to center of all BT's.

Office of..... County of.....
 State of....., I hereby certify that the within Instrument was filed in this office for record on the day of.....
 by
 (COUNTY OFFICIAL) (DEPUTY)

2-21