· · · · · · · · · · · · · · · · · · ·	-		Heordan Iels	Date	7100-52 (3	1/68) 5
Signature	Title	Division	Headquarters		<u> </u>	. 4
Estob. By	.1					
Y	. [					
x	. ]					
State Zone	.					
PLANE COORDINATE POSITION DATA	7					
Signature	rrom G11	.man ranch cab	oin go N <b>38</b> 0 E a	pprox. 700'to	corner.	
Ident. By	Erom C41	MNER LOCATION REL	ATIVE TO NEAR-BY	EATURES, ALSO HO	W TO REACH CO	RNER
Object ident	DESCRIPT OF	DA150 1000				3
Photo No Filed At.	- [					
PHOTO IDENTIFICATION DATA	1		•			
PHOTO IDENTIFICATION DATE	6		•			
			,			
\						
PLS 848	N.A.	ARING TREES OR O	THER OFFICIAL ACCES	SSORIES FOUND		
N 256 1980	DESCRIBE DE	APING TREES OF S	THEO OFFICE		·	2
CW-SW-NE 56						
S8		,				
T5S R30E			, LIGHE	<b>-</b>		
	Corne	r not previou	sly established	d	·	
CORNER DIAGRAM		tilla S	StateOre.			
MeridWillamette			ounty <u>Ilmatil</u>	la		
T55 R30E	– _ R.DUki	(Ref. FSM 715)	1.4) Surve	ey No	No	
Index $F/2 - 7/4$	COR	NER RECORD (S	EARCH) Tract	t or	Cor.	
USDA-FOREST SERVICE		•				

## CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

Set 3"x30" galv iron pipe with 3" brass cap 20" in the ground & placed a ring of stone around the pipe. Stamped brass cap as shown in the diagram.

		·		9		
ACCESSORIES DESCRIBE NEW BT's W	ITNESS OBJECTS ETC. ESTABL	ISHED, OR WORK DONE TO PRE	SERVE EXISTING EVIDENCE	CE		
From which A tamarack 7" dia. bea A fir 7" dia bears S 2 Nailed brass washers s painted red band aroun Set steel posts with b Bearing-True Grid	2 W 16.3 ft. stamped PLS 848 & be nd each tree.	aring tree signs to	each tree,	_10		
Work Done By D.M. Ferguson	Time Supervisor	Date 9-8-80 State Regis	stration No. PLS 848	· .		
Certified Cor-Regard Propered ? Tas	X No Filed At:		Date	11		
PROFESSIONAL	REMARKS					
LAND SURVEYOR	Witnesses to above corner.					
OREGON JULY 12, 1968 DOUGLAS M. FERGUSON		D. Herburger L. Wyllie				

Tract or Surv. No.

Cor. U.S. G.P.O. 1977-725-576