


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

J - 10

West 1/16, Sec. 9 and 16, T. 5 S., R. 34 E., W.M.

History of original corner establishment:

The West 1/16, Sec. 9 and 16, T. 5 S., R. 34 E., W.M. was originally monumented by James H. Hambleton (JHH) L.S. #645, in August, 1978. JHH's record states: "I set a 2 1/2" brass cap on a 30" galv. iron pipe, and being stamped as shown above, in a large mound of stone and dirt which buried the monument."



Description of corner evidence found:

I found a 2 1/2" diam. brass cap on a 2 1/2" galvanized iron pipe, 2" below the surface of the ground, marked

T5S  
W-1/16  
S 9  
S16  
R34E  
RLS 645 1978

From which: JHH BT's:

A stump, of a Lodgepole Pine, 7" (7") diam., bears N53°E (N50°E), a distance of 18.4 ft. (18.25 ft.).

Pieces of a Lodgepole Pine log, loose, 6" (6") diam., bears N36°W (N35 1/2°W), a distance of 23 ft. (23.33 ft.), scribed "/16S9 BT" visible, and brass washer marked "LS 645" nailed below the "BT".

Description of monument and accessories I established to perpetuate the original location of this corner:

From the existing brass cap I established the following new BT's: A Lodgepole Pine, 6" diam., bears N61°E, a distance of 5.3 ft., scribed "XBT", with a brass washer marked "LS 2211" nailed between the B & T.

A Lodgepole Pine, 8" diam., bears N25°W, a distance of 28.2 ft., scribed "W 1/16 S9 BT", with a brass washer marked "LS 2211" nailed between the B & T.

The brass cap is in a stone collar, which we re-build.

Set or reset steel fence posts: North 5 ft., and East 2.6 ft.

A cabin and 2 out buildings bear S40°W, about 300 ft.

REGISTERED PROFESSIONAL LAND SURVEYOR

Roger Green

OREGON JULY 17, 1986 ROGER O. GREEN 2211

Crew: Roger O. Green, Earl E. Strang  
Equipment: Kesson tape & staff compass.  
Field work: 9/17/91

Roger Green, L.S. 2211  
Wallowa-Whitman National Forest  
3502 Highway 30  
La Grande, OR 97850  
(503)963-7186

Note: Parenthetical information is Hambleton's record.

J-10

Office of..... County of.....  
State of....., I hereby certify that the within instrument was filed in this office  
for record on the..... day of....., 19.....  
..... by .....  
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

93-39-B

UNION COUNTY SURVEYOR  
Date Received 12/9/91  
Date Filed 12/12/91  
By Greg Blaker  
201-1991R

GPO-591-971, 1988

5-10  
Sec. 9, T5S, R34E  
September 30, 1991


DOG HAIR LODGEPOLE  
Property Boundary Conditions

A portion of Dog Hair Lodgepole, Units 1 & 2, maybe contiguous to the north-south center line of the Southwest 1/4 of Section 9, Township 5 South, Range 34 East, W.M., Union County, Oregon. This line was originally established by James Hambleton, LS 645, in 1978, based on evidence of the 1882 GLO survey by Rufus S. Moore.

We found the West 1/16 sec. cor. of sec. 9 & 16 and the Center West 1/16 sec. cor. of sec. 9. as established by Hambleton. Also we found the property boundary post between these two monuments. Maintenance work consisted of replacing signs on the boundary posts which had been rubbed off by cattle. In addition one new bearing tree was scribed at the C-W 1/16 and two were taken at the W 1/16.

As the work was accomplished we noted a "fence of convenience" which is located easterly from the property boundary (perhaps 100 feet on the north end and several hundred feet on the south).

Prepared by:



ROGER GREEN, LS 2211  
Zone Land Surveyor