

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

V-7

History of original corner establishment: Record of the orig. survey by J.W. Campbell, US Deputy Surveyor under his contract No. 468 dated April 12, 1883, states: Set post, 3 ft. long, 3 ins. square, 24 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ S on N. face, from which A fir, 24 ins. diam., bears N. 67° E., 59 lks. dist., marked $\frac{1}{4}$ SBT.

A tamarack, 10 ins. diam., bears S. 79° W., 11 lks. dist., marked $\frac{1}{4}$ S BT.

Dependent survey, portions of subdivisional lots by BLM under US Survey Group Nos. 350 and 643 dated August 21, 1967, states: The $\frac{1}{4}$ sec. cor. of Secs. 29 and 32, determined at record bearing and distance from the original remaining bearing tree: A larch, 19 ins. diam., bears S. 79° W., 11 lks. dist., with illegible Schiele marks visible on open blaze. At the corner point: Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap med: T6S R32E from which new bearing trees:

A fir, 7 ins. diam., bears N. 24° E., $29\frac{1}{2}$ lks. dist., med. $\frac{1}{4}$ S29 BT.


A fir, 9 ins. diam., bears S. 58° E., 30 lks. dist., med. $\frac{1}{4}$ S32 BT.

Description of corner evidence found: 3 $\frac{1}{2}$ " dia brass cap set on 2 $\frac{1}{2}$ in. iron post med: T6S R32E in a mound of stone. From which:

A larch, 20 ins. diam., bears S. $79^{\circ} 32'$ W., 7.30 ft. dist. (S. 79° W., 11 lks.) partially healed blaze

A fir, 14 ins. diam., bears S. $58^{\circ} 23'$ W., 19.30 ft. dist. (S. 58° E., 30 lks) healed blaze


A fir, 12 ins. diam., bears N. $24^{\circ} 28'$ E., 19.60 ft. dist. (N. 24° E., $29\frac{1}{2}$ lks.) healed blaze



$\frac{1}{4}$ 529
532
1968

Description of monument and accessories I established to perpetuate the original location of this corner: Reset all USFS 54-3 and 54-9 signs and painted 6" red band around BT5.
SET steel quad post, N. 90° E., 5 ft. dist., with USFS 54-2 and 54-9 signs attached. (4th witness)
Magnetic declination used to est. bearings at this corner: DC. 19° E
WITNESS: Ken Peters
Scott Keck

I hereby certify the above corner point was perpetuated in October 1990 as herein stated.



Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office
for record on the..... day of....., 19.....

David H. K. Lee..... by.....
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71)

RECEIVED BY

Umatilla County Surveyor

Date 3-91

Rec'd By X

No. 91-22-R