Index File No. X-01	CORNER RECORD ((Ref. FSM 715	•	act or rvey No. NFJD UNIT	Cor. No. AP-3302
T. 7S. R. 34 E. Merid. WILLAMETTE	R.D. North Fork John Day N.F. UMATILLA	County GRANT State OREGON		,
T75 R33E V4R34E	DESCRIBE CORNER MONUMENT Found a stone 18" by 12" b	FOUND	d of stone.	
536 531 RLS 2348	DESCRIBE BEARING TREES OR 24" Douglas Fir, N. 48° E., Root hole, with windthrown	36.0 ft., with healed f	ace.	· · · · · · · · · · · · · · · · · · ·
PHOTO IDENTIFICATION DATA Photo No.: Filed At.: Object Ident.: Ident. By: Signature PLANE COORDINATE POSITION State: Oregon Zone: North X: 2,472,644.07' Y: 461,377.34' Datum: NAD1927	DESCRIBE CORNER RELATIVE T From the jct. of roads 5505 2.28 miles to the end of the feet to the corner which is le	and 5505-170, travel road. From the end	southeasterly_on_550 of the road walk east	05-170 approx.
Signature D. Schlaich	Title Division Land Surveyor	Headquarters S.O.	Date 06/02/92	FS-7100-52 (3/68)

USDA-FOREST SERVICE

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT Set in place of the stone a 2 1/2" by 30" aluminum pipe, with 3 1/4" aluminum cap, 24" in the ground and surrounded it with a mound of stone (corner stone was placed in the mound of stone on the north side of the monument), mkd. "T7S R33E

ACCESSORIES: DESCRIBE NEW BT's WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE 7" Douglas Fir, S. 76° E., 37.5 ft., mkd. "1/4 S31""BT". 9" Lodgepole Pine, S. 55° W., 69.4 ft., mkd. "1/4 S36""BT".

6" Lodgepole Pine, S 89° W., 31.5 ft., mkd. "1/4 S36""BT".

New BT's are double blazed and have a 3/4" brass washer mkd. "RLS 2308" nailed next to the "BT" scribing on the lower blaze.

State Registration No. Work Done By D. Schlaich Title Land Surveyor Date 06/02/92 or Agency Cetified Cor. Record Prepared ? YES Filed At. Grant Co.

Date 08/31/92

REMARKS

Index File No. R. Tract or Survey No. Cor. X-01 7 S. 34 E. W.M. AP-3302 **NFJD UNIT**