· Dependent Resurvey of East Bdy. of T. 4 N., R. 27 E.

Chains

40.05 Proportionate measurement.

Set an iron post, 3 ft. long, 1 in. diam., 48 ins. in the ground, 1 ft. under surface of road, with broken glass deposited at the base, for $\frac{1}{4}$ sec. cor., with brass cap marked

At a point 25 lks. W. of true cor.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with broken glass deposited at the base, for witness cor. to the $\frac{1}{4}$ sec. cor., with brass cap marked



75.00 Irrigation canal, 30 lks. wide, course NW.

80.10 Proportionate measurement.

Set an iron post, 3 ft. long, 2 ins. diam., 48 ins. in the ground, 1 ft. under surface of road, with broken glass deposited at the base, for cor. of secs. 13, 18, 19, and 24, with brass cap marked

TL	IN .
R27E	R28E
S13 S24	S19
191	

At a point 25 lks. W. of true cor.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with broken glass deposited at the base, for witness cor. to the cor. of secs. 13, 18, 19, and 24, with brass cap marked

	IN	
R27E S13	R28E	WC
524 191	S19	25 W

Land, rolling. Soil, sandy, 2nd rate. No timber; undergrowth, sagebrush and greasewood.

North, bet. secs. 13 and 18.

Over rolling land, along road.

0.45 Irrigation ditch, 4 lks. wide, course W.

40.05 The $\frac{1}{4}$ sec. cor., which has been perpetuated with a basalt stone, lix12x8 ins., set below surface of road, and marked with a cross (x).

At point for cor.

Set an iron post, 3 ft. long, 1 in. diam., 48 ins. in the ground, 1 ft. below surface of road, with the basalt stone deposited